



Model VF750
Model VF1100

Indirect Fired Oil Heaters

- Reliable Riello burner
- Remote thermostat
- Wheels for easy portability
- Long lasting stainless steel combustion chamber
- High static centrifugal blower
- Ductable to 150 ft.
- Recirculation capability
- Available with 200 gallon fuel cell
- Very low noise fan ≤ 69 dB
- Includes flue stack



VF750 with optional 200 gallon fuel cell

SPECIFICATIONS		
	VF750	VF1100
	750,000 BTU/hr	1,000,000 BTU/hr
Fuel	#1 or #2 Diesel, Kerosene	#1 or #2 Diesel, Kerosene
Fuel Consumption	5.33 GPH	7.16 GPH
Burner	Riello 40 F20	Riello 40 F22
Electrical	208-240 Volts 20 Amps	208-240 Volts 25 Amps
Fan	9400 CFM, 1.2" Static Pressure, 3HP	11,200 CFM, 1.2" Static Pressure, 4HP
Thermostat	Remote On/Off with 50' cord	Remote On/Off with 50' cord
Temperature Rise	110°F	110°F
Dimensions	100"L x 36"W x 64"H	104"L x 41"W x 73"H
Duct Outlet (max duct length)	1-30" Dia. (150'), 2-20" Dia. (90')	1-30" Dia. (150'), 2-24" Dia. (90')
Duct Inlet (recirculation)	30" Dia., 30' Max Length	30" Dia., 30' Max Length
Approx. Weight	948 lbs.	1,160 lbs.



342 N. 400 E. Valparaiso, IN 46383
219-464-8818 • 219-462-7985 • www.heatwagon.com