

# Model IX405

## Indirect Fired Gas Heater

# SURE FLAME

- Built Sure Flame “Construction Tough” for long life and reliability
- Stackable design for efficient off season storage
- 16” puncture proof wheels for easy maneuverability
- Designed with return air recirculation for increased fuel savings
- 3 year warranty on combustion chamber
- Single stage external thermostat included
- Highest temperature rise and fan rating among other 400K IDF models
- Dual fuel selector valve enables quick change between propane and natural gas
- Operates on 15 amp, 120 V circuit




sold  
exclusively by

**heat wagon**

## Your Best Value In The Market!

See Product Comparison  
(on back)



### SPECIFICATIONS

Input	400,000 BTU/Hr
Fuel	Vapor Propane/Natural Gas
Gas Consumption	4.4 GPH Propane/400 CFH NG
Electrical	120 V, 12 Amps
Fan	5000 CFM
Thermostat	On/Off
Temp Rise	250° F @ 0°F Ambient
Rated Efficiency	90%
Dimensions	82" x 29" x 59"
Duct Size	2-12" or 1-16" outlets
Recirculation Inlet	16"
Weight	560 lbs.

**heat wagon**

342 N. 400 E. Valparaiso, IN 46383  
219-464-8818 • 219-462-7985 • [www.heatwagon.com](http://www.heatwagon.com)

# Product Comparison

Manufacturer	Frost Fighter, IDH400QR	Flagro, FV-400RC	Wacker, HI 400HD G	Sure Flame IX 405
<b>BTU input rate</b>	390,000	390,000	381,000(NG), 335,000 (LP)	400,000
<b>Blower fan volume Static pressure</b>	2800 CFM 2.8" WC	4000 CFM	3750 CFM 0.6" WC	5000 CFM 2.65" WC
<b>Duct</b>	2-12" outlets Ductable to 100'	2-12" outlets Ductable to 150'	1-20" outlet Ductable to 60'	2-12" outlets Ductable to 100'
<b>Fan type Fan HP</b>	Centrifugal blower 1.0 HP	Centrifugal blower 1.0 HP	Axial fan 1.0 HP	Centrifugal blower 1.0 HP
<b>Amp draw</b>	20 amp circuit	15 amp circuit	15 amp circuit	12 amps 15 amp circuit
<b>Flue stack included</b>	NO	NO	NO	YES
<b>Thermostat included</b>	NO	NO	NO	YES
<b>CSA certified</b>	YES	NO	YES	YES
<b>Combustion chamber Warranty</b>	ONE YEAR	ONE YEAR	ONE YEAR	THREE YEARS
<b>Recirculation capability</b>	YES	YES	YES	YES
<b>Temperature rise</b>	190 F at 0 degrees	150 F at 0 degrees	126 F at 0 degrees	250 F at 0 degrees
<b>Weight</b>	420 lbs	470 lbs	434 lbs	560 lbs
<b>Foot print</b>	70" x 32"	70" x 29" (14 sq ft)	81" x 34" (19.1 sq ft)	82" x 29" (16.5 sq ft) stackable design

\*Information above was obtained from manufacturers website for each product listed.